



Nepovratni ventil Serija MV33



Konstrukcija	Nepovratni ventil, v obliki vijačnega priključka s priključkom za cevko
Material	Telo Medenina, ponikljana, Tesnila NBR
Funkcija	prost prehod v eni smeri, blokirano v nasprotni smeri
Navojni priključki	M5 po ISO R/262, G1/8" do G1/2" po ISO228/1
Zunanji premer cevi	4mm, 6mm, 8mm, 10mm, 12mm in 14mm
priporočeni materiali	Poliamid (PA), Poliuretan (PU/CP), polietilen (PE), Poliamid – visoko fleksibilen (PF), PTFE (PT)
Tolerance cevi	+/-0,05 mm do premera 10 mm, +/-0,1 mm od premera 12 mm
Položaj vgradnje	poljubno
Medij	Stisnjen zrak, nevtralni plini
Temperatura medija	-10°C do +70°C
Obratovalni tlak	0,2 do 10 bar
Smer pretoka	prost prehod pri tlačnem dovodu na cevnem priključku, blokirano v nasprotni smeri

Dimenzije



ØT	D1	D2	L1	L2	CH	Teža [g]	Tip
4	M5	8	4	37,5	9	11	MV33-04-M5
4	G1/8"	13	6	31	11	14	MV33-04-18
6	G1/8"	13	6	38	13	21	MV33-06-18
8	G1/8"	16	8	39	14	27	MV33-08-18
6	G1/4"	13	6	39	15	25	MV33-06-14
8	G1/4"	16	8	40	16	30	MV33-08-14
10	G1/4"	16	8	43	18	37	MV33-10-14
10	G3/8"	20	9	43	18	43	MV33-10-38
12	G1/2"	25	10	47	22	68	MV33-12-12
14	G1/2"	25	10	54	25	85	MV33-14-12

Slike niso zavezujoče

Pridržujemo si pravico do sprememb konstrukcije, mer in materialov

Pnevmatika / Regulatorji pretoka in zaporni ventili / Protipovratni ventili / Protipovratni ventil serija MV33

Različica 7

138414 / Ustvarjeno 2026/33 SL

IZDELANO V EVROPI

+386 51 253 255

slovenia@stasto.eu

© STASTO AVTOMATIKA d.o.o.

www.stasto.si

Odpri serijo na spletu

Stran 1 / 1

