


Vijačni priključki - POM




Konstrukcija	Vijačni priključek z preklopno matico
Priključek	cilindrični navoj po ISO228/1 oziroma stožčasto po ISO7/1
Zunanji premer cevi	6mm...12mm
Materiali	Ohišje in vpenjalna matica iz polioksimetilena (POM)
priporočeno Materiali cevi	Poliamid (PA), Polietilen (PE), Poliuretan (CPU)
Medij	Plini in tekočine, ki kemično ne napadajo materialov
Temperatura medija	-10...+60°C
Obratovalni tlak	maks. 10bar

Ravno Vijačni priključek za privijanje - Navoj cilindričen


	Premjer cevi D / d [mm]	Priključek D1	CH1	CH2	L1	L2	Tip
	6/4	G1/8"	13	12	6,0	28	SC12-06-18-P
	6/4	G1/4"	17	12	7,9	30,5	SC12-06-14-P
	8/6	G1/8"	13	14	6,0	29,5	SC12-08-18-P
	8/6	G1/4"	17	14	7,9	32	SC12-08-14-P
	8/6	G3/8"	18,5	14	9,6	34	SC12-08-38-P
	10/8	G1/4"	18,5	17	9,4	34	SC12-10-14-P
	10/8	G3/8"	18,5	17	9,3	35,5	SC12-10-38-P
	12/9	G1/4"	19	19	9,8	37,5	SC12-12/9-14-P
	12/9	G3/8"	19	19	10,0	37,5	SC12-12/9-38-P

L-vrtljiva vijačna spojka- Navoj cilindričen


	Premjer cevi D / d [mm]	Priključek D1	CH1	CH2	L1	L2	Tip
	6/4	1/8"	12	14	31,7	27	SC14-06-18-PN
	6/4	1/4"	12	17	35,4	31	SC14-06-14-PN
	8/6	1/8"	14	14	33,3	27	SC14-08-18-PN
	8/6	1/4"	14	17	36,9	31	SC14-08-14-PN




Kotna vijačna priključna spojka - Stožčasti navoj

	Premjer cevi D / d [mm]	Priključek D1	CH1	L1	L2	Tip
	6/4	R1/8"	12	23	16	SC16C-06-18-P
	6/4	R1/4"	12	24	19	SC16C-06-14-P
	8/6	R1/8"	14	23	17	SC16C-08-18-P
	8/6	R1/4"	14	25	20	SC16C-08-14-P
	12/9	R1/4"	19	28	23	SC16C-12/9-14-P
	12/9	R3/8"	19	28	23	SC16C-12/9-38-P


T-vrtljiva vijačna spojka- Navoj cilindričen

	Premjer cevi D / d [mm]	Priključek D1	CH1	CH2	L1	L2	Tip
	6/4	G1/8"	14	12	47	27	SC22-06-18-PN
	6/4	G1/4"	17	12	51	31	SC22-06-14-PN
	8/6	G1/8"	14	14	49	27	SC22-08-18-PN
	8/6	G1/4"	17	14	53	31	SC22-08-14-PN


T-spojnik

	Premjer cevi D / d [mm]	CH1	D2	L1	L2	L3	L4	Tip
	6/4	12	4,3	52	26	7	5	SC29-06-P
	8/6	14	4,3	52	26	7	5	SC29-08-P
	12/9	19	4,3	63	32	9	5,8	SC29-12/9-P

Pregradni priključek


	Premjer cevi D / d [mm]	CH1	CH2	Navoj D1	L1	Tip
	6/4	12	14	M10x1	50	SC27-06-P
	8/6	14	16	M12x1	51	SC27-08-P
	12/9	19	21	M16x1	60	SC27-12/9-P

L-obročni kos

	Premjer cevi D / d [mm]	Priključek	L1	L2	L3	L4	Tip
	6/4	1/8"	31,7	15,8	16,3	15,7	SC35-06-18-P-X
	6/4	1/4"	35,4	19,7	16,3	19,5	SC35-06-14-P-X
	8/6	1/8"	33,3	16	16,4	15,8	SC35-08-18-P-X
	8/6	1/4"	36,9	19,6	16,3	19,5	SC35-08-14-P-X



Prekrivna matica

	Premjer cevi D / d [mm]	CH1	Navoj G	Tip
	6/4	12	M10x1	SC33-06-M10X1-P
	8/6	14	M12x1	SC33-08-M12X1-P
	10/8	17	M14x1	SC33-10-M14X1-P
	12/9	19	M16x1	SC33-12/9-M16X1-P

Ilustracije nezavezujoče

Pridržujemo si pravico do konstrukcijskih, dimenzijskih in materialnih sprememb

Pnevmatika / Vezni elementi in spojke / Navojni cevni priključki / Navojni cevni priključki - POM tlak 10bar, temperatura -10...+60°C

