

Prava navrtna spojnica Serija C-GAI-R



Osnovno telo sa maticom i sečnim prstenom



B4-Rezni prsten






B3-Rezni prsten

Konstrukcija	Priključak sa sečnim prstenom, sa B3 ili B4 prstenom za sečenje
Navoj za zavrtnje	1/8...1 1/2"
Spoljašnji prečnik cevi	6...42mm
Materijal	Čelik pocinkovano
Odgovarajuće standard	EN ISO 8434-1 (DIN 2353)
Medij	neutralne tečnosti i gasovi, koji ne napadaju upotrebljene materijale
Temperatura medijuma	B3-Rezni prsten -40...+120°C B4-Rezni prsten NBR -35...+100°C (FKM na upit)
Radni pritisak	Nazivni pritisak prema tabeli



Dimenzije



Osnovno telo

sa B4-rezni prsten

sa B3-rezni prsten

Seriya	PN [bar]	Prečnik cevi	G	L1	L2	L3	L4	CH1	CH2	Tip Osnovno telo	Tip sa B4-prstenom	Tip sa B3-prstenom
L	315	6	1/8	16	9	10	23,5	14	14	C-GAI06LR1/8X	C-GAI06ZLR1/8	C-GAI06LR1/8
		8	1/4	17	10	14	25	19	17	C-GAI08LR1/4X	C-GAI08ZLR1/4	C-GAI08LR1/4
		10	1/4	18	11	14	26	19	19	C-GAI10LR1/4X	C-GAI10ZLR1/4	C-GAI10LR1/4
		12	3/8	19	12	14	26,5	24	22	C-GAI12LR3/8X	C-GAI12ZLR3/8	C-GAI12LR3/8
		15	1/2	21	14	17	29	27	27	C-GAI15LR1/2X	C-GAI15ZLR1/2	C-GAI15LR1/2
		18	1/2	21	13,5	17	30	27	32	C-GAI18LR1/2X	C-GAI18ZLR1/2	C-GAI18LR1/2
	160	22	3/4	24	16,5	19	33	36	36	C-GAI22LR3/4X	C-GAI22ZLR3/4	C-GAI22LR3/4
		28	1	23,5	16	21,5	32,5	41	41	C-GAI28LR1X	C-GAI28ZLR1	C-GAI28LR1
		35	1 1/4	28,5	18	23,5	39,5	55	50	C-GAI35LR1 1/4X	C-GAI35ZLR1 1/4	C-GAI35LR1 1/4
		42	1 1/2	28,5	17,5	25,5	40,5	60	60	C-GAI42LR1 1/2X	C-GAI42ZLR1 1/2	C-GAI42LR1 1/2
	S	6	1/4	19	12	14	27	19	17	C-GAI06SR1/4X	C-GAI06ZSR1/4	C-GAI06SR1/4
		8	1/4	19	12	14	27	19	19	C-GAI08SR1/4X	C-GAI08ZSR1/4	C-GAI08SR1/4
		10	3/8	20	12,5	14	28,5	24	22	C-GAI10SR3/8X	C-GAI10ZSR3/8	C-GAI10SR3/8
		12	3/8	20	12,5	14	28,5	24	24	C-GAI12SR3/8X	C-GAI12ZSR3/8	C-GAI12SR3/8
		14	1/2	23	15	17	33	30	27	C-GAI14SR1/2X	C-GAI14ZSR1/2	C-GAI14SR1/2
		16	1/2	23	14,5	17	33	30	30	C-GAI16SR1/2X	C-GAI16ZSR1/2	C-GAI16SR1/2
		20	3/4	26	15,5	19	37	36	36	C-GAI20SR3/4X	C-GAI20ZSR3/4	C-GAI20SR3/4
		25	1	27,5	15,5	21,5	39,5	41	46	C-GAI25SR1X	C-GAI25ZSR1	C-GAI25SR1
		30	1 1/4	32,5	19	23,5	45,5	55	50	C-GAI30SR1 1/4X	C-GAI30ZSR1 1/4	C-GAI30SR1 1/4
		315	1 1/2	34,5	18,5	25,5	49,5	60	60	C-GAI38SR1 1/2X	C-GAI38ZSR1 1/2	C-GAI38SR1 1/2

Ilustracije neobavezujuće

Zadržavamo pravo na konstruktivne, dimenzione i materijalne izmene.

Pneumatika / Priključci i spojnice za pneumatiku / Priključci sa usečnim prstenom / priključak sa usečnim prstenom - pocinkovani čelik ISO 8434-1 (DIN 2353) / ravna spojnica sa unutrašnjim navojem serije C-GAI-R

Verzija 10

138469 / Generisano 2026/38 SR

PROIZVEDENO U EVROPI

+381 11 2399521

balkan@stasto.eu

© STASTO Automatizacija d.o.o.

www.stasto.rs

Otvori seriju online

Strana 2 / 2

