


Sealing screw Series C-VSTI-R-ED



Design type	Sealing screw
Male thread	1/8...1 1/2" BSP, with elastic seal
Material	Steel galvanized
according to standard	EN ISO 8434-1 (DIN 2353)
Seal	NBR (FKM on request)
Medium	neutral liquids and gases that do not attack the materials used
Medium temperature	-35...+100°C
Operating pressure	Nominal pressure according to table

Dimensions



Series	PN [bar]	G	D1	L1	L2	CH1	Type
S	400	1/8	14	12	8	5	C-VSTIR1/8ED
		1/4	19	17	12	6	C-VSTIR1/4ED
		3/8	22	17	12	8	C-VSTIR3/8ED
		1/2	27	19	14	10	C-VSTIR1/2ED
		3/4	32	21	16	12	C-VSTIR3/4ED
		1	40	22,5	16	17	C-VSTIR1ED
	250	1 1/4	50	22,5	16	22	C-VSTIR1 1/4ED
		1 1/2	55	22,5	16	24	C-VSTIR1 1/2ED

Illustrations non-binding

Design, dimensional and material changes reserved

Pneumatics / Fittings and couplings / Tube fittings / Tube fittings - Zinc plated steel ISO 8434-1 (DIN 2353) / Plug screw Series C-VSTI-R-ED

