


Sealing screw Series C-VSTI-M-ED



Design type	Sealing screw
Male thread	M10x1...M48x2, with elastic seal
Material	Steel galvanized
according to standard	EN ISO 8434-1 (DIN 2353)
Seal	NBR (FKM on request)
Medium	neutral liquids and gases that do not attack the materials used
Medium temperature	-35...+100°C
Operating pressure	Nominal pressure according to table

Dimensions



Series	PN [bar]	M	D1	L1	L2	CH1	Type
S	400	10x1	14	12	8	5	C-VSTIM10X1ED
		12x1,5	17	17	12	6	C-VSTIM12X1,5ED
		14x1,5	19	17	12	6	C-VSTIM14X1,5ED
		16x1,5	22	17	12	8	C-VSTIM16X1,5ED
		18x1,5	24	17	12	8	C-VSTIM18X1,5ED
		20x1,5	26	19	14	10	C-VSTIM20X1,5ED
		22x1,5	27	19	14	10	C-VSTIM22X1,5ED
		26x1,5	32	21	16	12	C-VSTIM26X1,5ED
		27x2	32	21	16	12	C-VSTIM27X2ED
		33x2	40	22,5	16	17	C-VSTIM33X2ED
	250	42x2	50	22,5	16	22	C-VSTIM42X2ED
		48x2	55	22,5	16	24	C-VSTIM48X2ED

Illustrations non-binding
Design, dimensional and material changes reserved

Pneumatics / Fittings and couplings / Tube fittings / Tube fittings - Zinc plated steel ISO 8434-1 (DIN 2353) / Plug screw Series C-VSTI-M-ED

