


plug screw series C-VSTI-M-ED-71



design	plug screw
male thread	M10x1...M48x2, with elastic sealing
material	stainless steel AISI 316Ti
according standard	EN ISO 8434-1 (DIN 2353)
seal	FKM
medium	neutral liquids and gases which do not affected the used material
medium temperature	-25...+200°C
operating pressure	nominal pressure according to table up to 50°C, above 50°C 4% pressure reduction, above 100°C 11% pressure reduction

dimensions



series	PN [bar]	M	D1	L1	L2	CH1	type
S	400	10x1	14	12	8	5	C-VSTIM10X1ED71
		12x1,5	17	17	12	6	C-VSTIM12X1,5ED71
		14x1,5	19	17	12	6	C-VSTIM14X1,5ED71
		16x1,5	22	17	12	8	C-VSTIM16X1,5ED71
		18x1,5	24	17	12	8	C-VSTIM18X1,5ED71
		20x1,5	26	19	14	10	C-VSTIM20X1,5ED71
		22x1,5	27	19	14	10	C-VSTIM22X1,5ED71
		26x1,5	32	21	16	12	C-VSTIM26X1,5ED71
		27x2	32	21	16	12	C-VSTIM27X2ED71
		33x2	40	22,5	16	17	C-VSTIM33X2ED71
	250	42x2	50	22,5	16	22	C-VSTIM42X2ED71
		48x2	55	22,5	16	24	C-VSTIM48X2ED71

illustrations are for information only and are non-binding
all designs, configurations, measurements and materials are subject to change without prior notice