

Partnership. With Guarantee.

3/2-Way coaxial solenoid valve - direct-acting, DN65 Series CVF3-65





normally closed (NC)




normally open (NO)

Design type	3/2-way coaxial solenoid valve, direct-acting, normally closed or normally open
Mode of operation	pressure-relieved, with spring return, non-overlapping
Nominal size	DN 65mm
Connection	CVF3: Flange PN16, Special flanges on request
Pressure range	0-16bar, A → B max. 16bar / B → A max. 5bar / A → C max. 16bar / C → A max. 16bar
Back pressure	P2 > P1, see pressure range
Materials	optional Body Aluminium, Nickel-plated steel, Galvanized steel or Stainless steel Valve seat Plastic on metal, Sealing materials NBR, PTFE, FPM, EPDM The material specifications of the versions refer exclusively to the valve connection parts in contact with the medium
Media	gaseous - liquid - high-viscosity - gelatinous - contaminated
Flow direction	see pressure range
Mounting type	Installation in rigid piping system
Mounting position	any
Vacuum Leakage rate	< 10 $^{-4}$ mbar*l*s $^{-1}$
Kv value	40,0m³/h
Switching cycles	20/min.
Switching time	ON 600ms, CLOSED 800ms
Medium temperature	-20...+80°C
Ambient temperature	-20...+80°C
Approvals	on request LR/GL/EN10204
Weight	47,6kg
Options	Vacuum tests with certificate, Limit switch inductive (Normally closed (NC) PNP- Icomatic/Balluf)


+43 512 52076
austria@stasto.eu
© STASTO Automation KG

Voltage type	AC and DC voltage
Standard voltage	230V/40-60Hz, 24VDC, Permissible voltage fluctuation ±10%
Special voltages	on request
Solenoid system	DC DC solenoid, AC DC solenoid with integrated rectifier
Insulation class	H 180°C
Current consumption	N-coil 24VDC 4,40A, 230VAC 0,65A, H-coil 230VAC 0,79A
Duty cycle	100% duty cycle (continuous operation)
Degree of protection	IP65 according to EN 60529 with correctly mounted device connector (protection against dust ingress and water jets)
Scope of delivery	incl. connector according to EN175301-803 Form A (formerly DIN43650)-Cable entry M16x1,5
optional	Terminal box M16x1,5 on request
Additional equipment	Illuminated connector with varistor
Ordering information	Nominal size, Connection, Function NC/NO, Operating pressure, Flow rate, Medium, Medium temperature, Ambient temperature, Rated voltage, Rated voltage Limit switch
Application note	The technical design of the valves is media- and application-specific, which may result in deviations from the general specifications stated in the data sheet with regard to version, sealing materials and characteristic values. In the event of inaccurate or incomplete ordering information or application data, there is a risk of incorrect technical sizing of the valves for the intended application purpose. This may result in the physical and/or chemical properties of the materials or seals used being insufficient for the intended application purpose.

Dimensions



CVF3-65 Function NC




CVF3-65 Function NO

Flange PN	DIN	ØD	Øk	Ød
16	EN 1092-1	185	145	18

Electrical connections



DIN EN 175301-803



Terminal box



Form A connector
DIN EN 175301-803

Limit switch



Icomatic Plastic version
M12x1, DC 10 - 60V
AC 15 - 250V
-25...+85°C



Balluff Metal version
M12x1, DC 10 - 30V
-25...+70°C

Illustrations non-binding
Design, dimensional and material changes reserved

+43 512 52076
austria@stasto.eu
© STASTO Automation KG