


axial type check valve made of stainless steel series CH006



design	seat valve spring loaded
connection	G3/8"...G2" according to ISO228/1
materials	body stainless steel AISI 316, inner parts stainless steel AISI 316, seal PTFE
medium temperature	-30...+130°C
type of fixing	installed into rigid pipework
mounting position	any
flow direction	free in arrow direction, in opposite direction closed
application	group 1 and 2 liquids acc. to PED 2014/68/EU and which do not affect the used materials



connection A	nominal diameter [mm]	pressure range [bar]	D	I	L	SW	kv value [m ³ /h]	weight [app. kg]	type
G3/8"	12	0,1-16	32	12	58	22	4,3	0,24	CH006-38
G1/2"	15	0,1-16	35	14	65,2	27	5,4	0,28	CH006-12
G3/4"	20	0,1-16	45	18	80	36	13,0	0,57	CH006-34
G1"	25	0,1-16	50	18	96,5	40	20,5	0,70	CH006-10
G1 1/4"	32	0,1-16	59	18	100	52	33,0	1,02	CH006-114
G1 1/2"	40	0,1-16	70	18	110	52	44,0	1,52	CH006-112
G2"	50	0,1-16	85	22	130	77	59,0	2,32	CH006-20
G2 1/2"	65	0,1-16	110		140		64,5		CH006-212

illustrations are non-binding
all designs, configurations, measurements and materials are subject to change without prior notice