


spojnica DN 7,2mm serije C0.S72-H




tip konstrukcije	spojnica i čep spojnice, dvosmerno zaptivanje
nominalni otvor	DN 7,2mm
materijali	telo, ventil i konektor nerđajući čelik AISI 303, opruga napravljena od nerđajućeg čelika AISI 304, zaptivka FKM
protok	komprimovani vazduh max.1200NI/min pri 6 bara (Δp 0,5bar), voda 10l/min (Δp 0,5bar)
medijum	gasovi i tečnosti koje ne ustiču na korišćene materijale
temperatura medija	-20°C...+200°C
radni pritisak	-0,80...35bar


C0CS72-M spojnica - muški navoj

	D1	D2	L1	L2	CH	težina [g]	tip
	G1/4"	27	9	41	22	82	C0CS72-M14-H
	G3/8"	27	10	42	22	82	C0CS72-M38-H
	G1/2"	27	12	44	24	95	C0CS72-M12-H


C0CS72-F spojnica - unutrašnji navoj

	D1	D2	L1	L2	CH	težina [g]	tip
	G1/4"	27	10,5	41,5	22	83	C0CS72-F14-H
	G3/8"	27	10,5	41,5	22	83	C0CS72-F38-H
	G1/2"	27	12	43	24	92	C0CS72-F12-H


C0CS72-H spojnica - mlaznica creva

	unutrašnji prečnik creva	D1	D2	L2	CH	težina [g]	tip
	6	7,5	27	56	22	92	C0CS72-H06-H
	9	10,5	27	56	22	92	C0CS72-H09-H
	13	14,5	27	56	22	95	C0CS72-H13-H


C0PS72-M čep spojnice - muški navoj

	D1	L1	CH	težina [g]	tip
	G1/4"	43	22	52	C0PS72-M14-H
	G3/8"	45	22	55	C0PS72-M38-H
	G1/2"	47	24	62	C0PS72-M12-H

C0PS72-F čep spojnice - unutrašnji navoj

	D1	L1	CH	težina [g]	tip
	G1/4"	44	22	55	C0PS72-F14-H
	G3/8"	44	22	55	C0PS72-F38-H
	G1/2"	45,5	24	62	C0PS72-F12-H

C0PS72-H čep spojnice - mlaznica creva

	unutrašnji prečnik creva	D1	L1	CH	težina [g]	tip
	6	7,5	54	22	55	C0PS72-H06-H
	9	10,5	54	22	55	C0PS72-H09-H
	13	14,5	54	22	57	C0PS72-H13-H

ilustracije su samo za informaciju i bez obaveza
sve konstrukcije, konfiguracije, mere i materijali podležu promenama bez prethodne najave