


Spojke Serija CI.S-S



Konstrukcija	Vtičnice sklopov in vtiči sklopov, obojestransko zaporno, ISO 7241-1 Serija B
Materiali	Ohišje, ventil in konektor Nerjavno jeklo 1.4401, Vzmet Nerjavno jeklo 1.4401, Tesnilo FKM
Medij	Plini in tekočine, ki ne napadajo uporabljenih materialov
Temperatura medija	-20...+200°C
Obratovalni tlak	glej tabelo

CICS-F Vtičnica sklopke - notranji navoj

	A	DN [mm]	Velikost	D	L	L1	SW	maks. obratovalni tlak [bar]	Pretok [l/min]	Teža [g]	Tip
	G1/4"	6,3	04	28	56	10	19	350	14	125	CICS1/4-F14-S
	G3/8"	10	06	35	64	11,5	24	270	27	227	CICS3/8-F38-S
	G1/2"	12,5	08	44	71,5	16	30	320	60	385	CICS1/2-F12-S
	G3/4"	20	12	52	89	18	36	250	110	634	CICS3/4-F34-S
	G1"	25	16	60	106	20	41	210	150	922	CICS1-F10-S

CIPS-F Vtičnica sklopke - notranji navoj


	A	DN [mm]	Velikost	L	L1	SW	maks. obratovalni tlak [bar]	Pretok [l/min]	Teža [g]	Tip
	G1/4"	6,3	04	35	10	19	350	14	35	CIPS1/4-F14-S
	G3/8"	10	06	39	11,5	22	270	27	60	CIPS3/8-F38-S
	G1/2"	12,5	08	44	16	27	320	60	101	CIPS1/2-F12-S
	G3/4"	20	12	55	18	36	250	110	206	CIPS3/4-F34-S
	G1"	25	16	66	20	41	210	150	378	CIPS1-F10-S

Diagram padca tlaka

