


Sealing screw Series A-VSTI-M-ED-71



Design type	Sealing screw
Male thread	M10x1...M48x2, with elastic seal
Material	Stainless steel 1.4571
according to standard	EN ISO 8434-1 (DIN 2353)
Seal	FKM
Medium	neutral liquids and gases that do not attack the materials used
Medium temperature	-25...+200°C
Operating pressure	Nominal pressure according to table up to 50°C, above 50°C 4,5% Pressure reduction, above 100°C 11% Pressure reduction

Dimensions



Series	PN [bar]	M	D1	L1	L2	CH1	Type
S	400	10x1	14	12,3	8	5	A-VSTIM10X1ED71
		12x1,5	17	17,3	12	6	A-VSTIM12X1,5ED71
		14x1,5	19	17,3	12	6	A-VSTIM14X1,5ED71
		16x1,5	22	17,3	12	8	A-VSTIM16X1,5ED71
		18x1,5	24	17,3	12	8	A-VSTIM18X1,5ED71
		20x1,5	26	19,3	14	10	A-VSTIM20X1,5ED71
		22x1,5	27	19,3	14	10	A-VSTIM22X1,5ED71
		26x1,5	32	21,3	16	12	A-VSTIM26X1,5ED71
		27x2	32	21,3	16	12	A-VSTIM27X2ED71
		33x2	40	22,8	16	17	A-VSTIM33X2ED71
	250	42x2	50	22,8	16	22	A-VSTIM42X2ED71
		48x2	55	22,8	16	24	A-VSTIM48X2ED71

Illustrations non-binding

Design, dimensional and material changes reserved

