


Couplings DN 7,2mm Series C0.72-N




Design type	Coupling sockets and coupling plugs, single shut-off
Nominal size	DN 7,2mm
Materials	Body, valve and connector Nickel-plated brass, Stainless steel spring 1.4310, Seal NBR
Nominal flow rate	960Nl/min at 6 bar (Δp 0,5bar)
Medium	Compressed air, neutral gases and liquids
Medium temperature	-20...+100°C
Operating pressure	-0,87...35bar


C0C72-M Coupling socket - Male thread

	D1	D2	L1	L2	CH	Weight [g]	Type
	G1/8"	27	7	38	22	70	C0C72-M18-N
	G1/4"	27	9	39	22	73	C0C72-M14-N
	G3/8"	27	9	41	22	76	C0C72-M38-N
	G1/2"	27	10	44	24	87	C0C72-M12-N

C0C72-F Coupling socket - Female thread


	D1	D2	L1	L2	CH	Weight [g]	Type
	G1/4"	27	9	39	22	90	C0C72-F18-N
	G1/4"	27	10,5	41	22	92	C0C72-F14-N
	G3/8"	27	10,5	41	22	85	C0C72-F38-N
	G1/2"	27	12	43	24	87	C0C72-F12-N

C0C72-H Coupling socket - Hose nozzle


	Hose inner diameter	D2	L2	Weight [g]	Type
	6	27	55	64	C0C72-H06-N
	8	27	55	67	C0C72-H08-N
	9	27	55	68	C0C72-H09-N
	10	27	55	70	C0C72-H10-N
	13	27	55	75	C0C72-H13-N




C0P72-M Coupling plug - Male thread

	D1	L1	CH	Weight [g]	Type
	G1/8"	31	13	17	C0P72-M18-N
	G1/4"	33	17	21	C0P72-M14-N
	G3/8"	33	19	26	C0P72-M38-N
	G1/2"	35	24	41	C0P72-M12-N

C0P72-F Coupling plug - Female thread

	D1	L1	CH	Weight [g]	Type
	G1/8"	30	13	19	C0P72-F18-N
	G1/4"	33	17	26	C0P72-F14-N
	G3/8"	33	19	26	C0P72-F38-N
	G1/2"	35	24	37	C0P72-F12-N

C0P72-S Coupling plug - Hose connection

	D1	L1	Weight [g]	Type
	6/4	34	18	C0P72-S06-N
	8/6	34	19	C0P72-S08-N
	10/8	43	38	C0P72-S10-N-A

C0P72-H Coupling plug - Hose nozzle

	Hose inner diameter	L1	Weight [g]	Type
	6	44	14	C0P72-H06-N
	8	44	18	C0P72-H08-N
	9	44	17	C0P72-H09-N
	10	44	19	C0P72-H10-N
	13	44	24	C0P72-H13-N

Illustrations non-binding

Design, dimensional and material changes reserved

Pneumatics / Fittings and couplings / Couplings / Coupling plug Standard / Couplings DN 7,2 - Nickel plated brass

