Partnership. With Guarantee.

Straight intermediate nipple
Series C-GZ

Design type	Compression fitting with cutting ring with sealing cone and O-ring
Tube outside diameter	6...42mm
Material	Steel galvanized
according to standard	EN ISO 8434-1 (DIN 2353)
Seal	NBR (FKM on request)
Medium	neutral liquids and gases that do not attack the materials used
Medium temperature	-35..+100°C
Operating pressure	Nominal pressure according to table

Dimensions



Series	PN [bar]	Tube diameter	m	L1	CH1	Type
L	500	6	12x1,5	40	14	C-GZ06L
		8	14x1,5	40	17	C-GZ08L
		10	16x1,5	40	19	C-GZ10L
	400	12	18x1,5	40	22	C-GZ12L
		15	22x1,5	44	27	C-GZ15L
		18	26x1,5	43	32	C-GZ18L
	250	22	30x2	50	36	C-GZ22L
		28	36x2	51	41	C-GZ28L
		35	45x2	62	50	C-GZ35L
		42	52x2	62	60	C-GZ42L
S	800	6	14x1,5	41	17	C-GZ06S
		8	16x1,5	41	19	C-GZ08S
		10	18x1,5	44	22	C-GZ10S
	630	12	20x1,5	45	24	C-GZ12S
		14	22x1,5	49	27	C-GZ14S
		16	24x1,5	52	30	C-GZ16S
	420	20	30x2	61	36	C-GZ20S
		25	36x2	68	46	C-GZ25S
		30	42x2	74	50	C-GZ30S
		38	52x2	83	60	C-GZ38S

+43 512 52076
austria@stasto.eu
© STASTO Automation KG

+43 512 52076
austria@stasto.eu
© STASTO Automation KG