


Welding cone Series C-SKA



Design type	Compression fitting with cutting ring, with sealing cone and O-ring
Tube outside diameter	6...42mm
Material	Steel galvanized
according to standard	EN ISO 8434-1 (DIN 2353)
Seal	NBR (FKM on request)
Medium	neutral liquids and gases that do not attack the materials used
Medium temperature	-35...+100°C
Operating pressure	Nominal pressure according to table


Dimensions



Series	PN [bar]	Tube diameter	L1	D1	D2	Type
L/S	630	6	31	2,5	6	C-SKA6x1,75
		8	31	4	8	C-SKA8x2
	315	10	32,5	7	10	C-SKA10x1,5
	400	10	32,5	6	10	C-SKA10x2
	315	12	32,5	9	12	C-SKA12x1,5
	400	12	32,5	8	12	C-SKA12x2
	630	12	32,5	7	12	C-SKA12x2,5
L	315	15	34	10	15	C-SKA15x2,5
		18	35,5	13	18	C-SKA18x2,5
	160	22	38,5	17	22	C-SKA22x2,5
		28	41,5	23	28	C-SKA28x2,5
		35	47,5	29	35	C-SKA35x3
		42	47,5	36	42	C-SKA42x3



Dimensions



Series	PN [bar]	Tube diameter	L1	D1	D2	Type
S	400	14	38,5	8	14	C-SKA14x3
	250	16	39	12	16	C-SKA16x2
	315	16	39	11	16	C-SKA16x2,5
	400	16	39	10	16	C-SKA16x3
	250	20	45	15	20	C-SKA20x2,5
	315	20	45	14	20	C-SKA20x3
	400	20	45	12	20	C-SKA20x4
	250	25	49,5	19	25	C-SKA25x3
	315	25	49,5	17	25	C-SKA25x4
	400	25	49,5	15	25	C-SKA25x5
	160	30	52	24	30	C-SKA30x3
	250	30	52	22	30	C-SKA30x4
	315	30	52	20	30	C-SKA30x5
		30	52	18	30	C-SKA30x6
	160	38	56,5	32	38	C-SKA38x3
	250	38	56,5	28	38	C-SKA38x5
	315	38	56,5	26	38	C-SKA38x6
		38	56,5	22	38	C-SKA38x7

Illustrations non-binding

Design, dimensional and material changes reserved

[Pneumatics](#) / [Fittings and couplings](#) / [Tube fittings](#) / [Tube fittings - Zinc plated steel ISO 8434-1 \(DIN 2353\)](#) / [Weld-on cone Series C-SKA](#)

Version 6

138498 / Generated 2026/33 EN

MADE IN EUROPE

+43 512 52076

austria@stasto.eu

© STASTO Automation KG

www.stasto.com

Open series online

Page 2 / 2

