




2/2-Way coaxial valve - pilot-operated, DN15 Series CVTE/CVFE-15



Type designation	CVTE-15, CVFE-15, with pilot valve CVTE-P-15, CVFE-P-15,
Design type	2/2-way coaxial valve, pilot-operated, normally closed (de-energized closed) or de-energized open
Mode of operation	pressure-relieved, with spring return
Nominal size	DN 15mm
Connection	CVTE: G3/8"...G3/4", CVFE: Flanges PN16/40/100, Special flanges and threads on request
Pressure range	0...16, 0...40, 0...63 or 0...100bar, > 100bar on request
Back pressure	P2 > P1, available (max. 16bar)
Materials	optional Body Brass, Brass nickel-plated, Steel nickel-plated, Steel galvanized, non-ferrous metal-free or Stainless steel Valve seat Plastic on metal, Sealing materials PTFE, NBR, FPM, CR, EPDM The material specifications of the versions refer exclusively to the valve connection parts that come into contact with the medium
Media	gaseous - liquid - contaminated - high-viscosity - gelatinous - paste-like
Flow direction	A → B, according to Marking, (Special version alternating max. 16bar)
Mounting type	Installation in rigid piping system, Mounting bracket on request
Mounting position	any
Vacuum Leakage rate	< 10 ⁻⁶ mbar*l*s ⁻¹
Kv value	5,7m ³ /h
Switching cycles	200/min.
Switching time	ON 50...3000ms, CLOSED 50...3000ms
Cushioning	ON/CLOSED: via throttling of the pilot valve
Medium temperature	with flange-mounted pilot valve up to +60°C (Pilot valve outside the temperature range medium temperature max. 160°C)
Ambient temperature	with flange-mounted pilot valve up to +50°C
Manual emergency override	via pilot valve
Approvals	on request LR/DNV/EN10204
Weight	CVTE 3,4kg, CVFE 5,0kg
Options	Vacuum tests with certificate, Limit switch inductive (Normally closed (NC) PNP- Icomatic/Balluff), Limit switch inductive NAMUR (+ Switching amplifier), Limit switch mechanical (Changeover contact), Flushing ports, Leakage ports, modular design, Version ATEX Ex II 2G Ex h IIC T6...T3 Gb / Ex II 2D Ex h IIIC T-40°C...+195°C Db



Voltage type	AC and DC voltage
Standard voltage	230V/50Hz, 24VDC, Permissible voltage fluctuation $\pm 10\%$
Special voltages	on request
Power consumption	DC: 4,8W (2,5W on request), AC: Tightening torque 11,0VA, Holding force 8,5VA
Duty cycle	100% (Continuous operation)
Degree of protection	IP65 according to EN 60529 with properly mounted device socket connector (Protection against dust ingress and water jets)
Scope of delivery	incl. connector according to EN175301-803-Form B or rather Industrial design form - Cable entry M16x1,5
optional	Solenoid coil M12-DESINA, Solenoid coil M12-VDMA
Additional equipment	Illuminated connector with varistor
Explosion protection optional	ATEX Ex II 2G Ex mb IIC T5 Gb, Ex II 2D Ex mb tb IIIC T95°C IP66 Db Power consumption 24VDC: 3,25W, 230VAC: 2,9W
	Actuation pneumatic
Pilot pressure range	4...8bar
Air consumption	11cm ³ /Stroke
Switching speed	Main valve infinitely adjustable via throttles of the pilot valve
Control	preferably via 5/2-way pilot valve
Connection diagram	co-ax/NAMUR, (ISO 1 on request)
Control ports	2/4: G1/8" (G1/4" on request)
	Actuation hydraulic
Pilot pressure range	15...30bar/30...60bar
Control	preferably via 4/2-way pilot valve
Control ports	X/Y: G1/4" (NPT 1/4 on request)
Ordering information	Nominal size, Connection, Function NC/NO, Operating pressure, Flow rate, Medium, Medium temperature, Ambient temperature, Rated voltage, Rated voltage Limit switch, Actuation
Application note	The technical design of the valves is media- and application-specific, which may result in deviations from the general information stated in the data sheet with regard to version, sealing materials and characteristic values.. In the case of inaccurate or incomplete ordering information or application data, there is a risk of incorrect technical sizing of the valves for the intended application.. This may result in the physical and/or chemical properties of the materials or seals used being insufficient for the intended application purpose.



Dimensions

CVTE-15 Function NC

CVFE-15 Function NO

Mounting brackets must be ordered separately

Installation lengths	L1	L2	L3
Standard	186	135	243
with 1/2 inductive limit switches	212	161	269
with pressure lubricator head	219	168	276
with mechanical limit switches	212	161	269

Flange PN	DIN	ØD	Øk	Ød
16	EN 1092-1	95	65	14
40	EN 1092-1	95	65	14
100	EN 1092-1	105	75	14

Pilot valves

Pilot valve ABS56
5/2-way valve NAMUR,
electropneumatic,
G1/4, with exhaust air flow controls,
p = 4...10bar

Pilot valve
5/2-way valve NAMUR,
electropneumatic,
G1/8, with exhaust air flow controls,
p = 4...10bar

Pilot valve
5/2-way valve ISO1,
electropneumatic,
G1/4,
p = 4...10bar

Pilot valve
5/2-way valve co-ax,
electropneumatic,
G1/4,
p = 4...10bar

Electrical connections

electrical connection
Solenoid coil M12x1

electrical connection
Form B connector DIN EN 175301-803
or rather Industrial design form

Limit switch

Icomatic Plastic version
M12x1, DC 10...60V
AC 15...250V
-25...+85°C

Balluff Metal version
M12x1, DC 10...30V
-25...+70°C

Honeywell
Changeover contact

Illustrations non-binding
Design, dimensional and material changes reserved

Armatures / Special armatures / Coaxial valves / 2/2-way-coaxial valves Series CVTC.../CVTEH.../CVTE.../CVFE.../CVTV.../CVFV.../CVFF... / [CVTE-15...] 2/2-way-coaxial valves CVTE-15...