


Retningsventiler med fodbetjening Serie PM122, PM137, PM138



PM122






PM138






PM137

Konstruktionstype	PM122/PM138 Skydeventil, PM137 Sædeventil, med fodbetjening
Tilslutning	G1/4" iht. ISO228/1 hhv. 4mm Push-in-forskruning
Nominal diameter	PM122/PM138 DN8mm, PM137 DN2,5mm
Medium	filtreret og oliesmurt eller uoliesmurt trykluft
Medietemperatur	0...+40°C
Gennemstrømning	PM122/PM138 1080NI/min, PM137 90NI/min
Omgivelsestemperatur	-10...+50°C
Driftstryk	PM122/PM138 3...10bar, PM137 0...10bar
Bemærk	CAD-filer fås i STASTO Store på www.stasto.eu



PM122 5/2-vejsventil G1/4"

		Aktivering	Type
		Fod/fjeder	PM122-14
		Fod/låsende	PM122-14-BS

PM138 5/2-vejsventil G1/4"

		Aktivering	Type
		Fod/fjeder	PM138-14
		Fod/låsende	PM138-14-BS

PM137 3/2-vejsventil 4mm Push-in-forskruning

		Aktivering	Type
		Fod/fjeder	PM137-04

Illustrationer ikke bindende

Konstruktions-, mål- og materialeændringer forbeholdes



