



Razvodni ventili s nožnim upravljanjem Serija PM122, PM137, PM138



PM122






PM138





PM137

Izvedba	PM122/PM138 Klizni ventil, PM137 Ventil sa sjedištem, s nožnim upravljanjem
Priključak	G1/4" prema ISO228/1 odnosno 4mm Priključak na utiskivanje
Nazivni promjer	PM122/PM138 DN8mm, PM137 DN2,5mm
Medij	filtrirani i podmazani ili nepodmazani komprimirani zrak
Temperatura medija	0...+40°C
Protok	PM122/PM138 1080NI/min, PM137 90NI/min
Temperatura okoline	-10...+50°C
Radni tlak	PM122/PM138 3...10bar, PM137 0...10bar
Napomena	CAD-datoteke dostupne su u STASTO Storeu na www.stasto.eu



PM122 5/2-putni ventil G1/4"

		Aktiviranje	Tip
		Nožica/opruga	PM122-14
		Nožna/položajno zadržavanje	PM122-14-BS

PM138 5/2-putni ventil G1/4"

		Aktiviranje	Tip
		Nožica/opruga	PM138-14
		Nožna/položajno zadržavanje	PM138-14-BS

PM137 3/2-putni ventil 4mm Priključak na utiskivanje

		Aktiviranje	Tip
		Nožica/opruga	PM137-04

Ilustracije neobvezujuće

Zadržavamo pravo na konstrukcijske, dimenzijske i materijalne izmjene.



