



Zaporni ventilni priključek Serija MV55



Konstrukcija	Zaporni ventil, v obliki vijačnega priključka s priključkom za cevko
Material	Telo Medenina, ponikljana, Tesnila NBR
Funkcija	Z vstavitvijo cevi se odpre notranji ventil. Ob sprostitvi cevi se pretok samodejno zapre.
Navojni priključki	G1/8" ... G1/4" po ISO228/1
Zunanji premer cevi	6mm in 8mm
priporočeni materiali	Poliamid (PA), Poliuretan (PU/CP), polietilen (PE), PTFE (PT)
Tolerance cevi	+/-0,05mm do premera 10mm, +/-0,1 mm od premera 12mm
Položaj vgradnje	poljubno
Medij	Stisnjen zrak, nevtralni plini
Temperatura medija	-20...+70°C
Obratovalni tlak	maksimalno 10bar

Dimenzije



D1	D2	D3	L1	L2	CH	Pretok [Nl/min]	Teža [g]	Tip
G1/8"	13,5	6	5	27	12	365	15	MV55-06-18
G1/8"	16	8	6,5	27	12	365	18	MV55-08-18
G1/4"	13,5	6	5	27,5	13	380	18	MV55-06-14
G1/4"	16	8	6,5	27,5	13	380	21	MV55-08-14

Slike niso zavezujoče

Pridržujemo si pravico do sprememb konstrukcije, mer in materialov

