


BSP-Adapter BSI 5200




Priključak	1/8"...2"BSP
Materijal	Pocinčani čelik, elastična zaptivka odnosno O-prsten NBR
Medij	Komprimovani vazduh, neutralni gasovi, Tečnosti koje hemijski ne napadaju materijale
Temperatura medijuma	-40°C...+120°C, elastična zaptivka odnosno O-prsten NBR -35°C...+100°C
Radni pritisak	Nazivni pritisak prema tabeli



Dupli nipel Serija 3005

	PN [bar]	A	B	L1	L2	L3	CH1	Tip
400	1/8	1/8	1/8	24	8	8	14	300501
400	1/8	1/4	1/4	28,5	8	11	19	300502
400	1/8	3/8	3/8	30	8	12	22	300503
350	1/8	1/2	1/2	33,5	8	14	27	300532
400	1/4	1/4	1/4	32	11	11	19	300504
400	1/4	3/8	3/8	33,5	11	12	22	300505
350	1/4	1/2	1/2	37	11	14	27	300506
350	1/4	5/8	5/8	39	11	16	30	300533
315	1/4	3/4	3/4	41	11	16	32	300507
250	1/4	1	1	45	11	19	41	300534
400	3/8	3/8	3/8	35	12	12	22	300508
350	3/8	1/2	1/2	38,5	12	14	27	300509
350	3/8	5/8	5/8	40,5	12	16	30	300535
315	3/8	3/4	3/4	42,5	12	16	32	300510
250	3/8	1	1	46,5	12	19	41	300536
350	1/2	1/2	1/2	41	14	14	27	300511
350	1/2	5/8	5/8	43	14	16	30	300512
315	1/2	3/4	3/4	45	14	16	32	300513
250	1/2	1	1	49	14	19	41	300514
200	1/2	1 1/4	1 1/4	52	14	20	50	300515
160	1/2	1 1/2	1 1/2	57	14	23	55	300537
350	5/8	5/8	5/8	45	16	16	30	300516
315	5/8	3/4	3/4	47	16	16	32	300517
250	5/8	1	1	51	16	19	41	300538
200	5/8	1 1/4	1 1/4	54	16	20	50	300539
315	3/4	3/4	3/4	47	16	16	32	300518
250	3/4	1	1	51	16	19	41	300519

Dupli nipel Serija 3005

	PN [bar]	A	B	L1	L2	L3	CH1	Tip
200	3/4	1 1/4	1 1/4	54	16	20	50	300520
160	3/4	1 1/2	1 1/2	59	16	23	55	300521
250	1	1	1	54	19	19	41	300522
200	1	1 1/4	1 1/4	57	19	20	50	300523
160	1	1 1/2	1 1/2	62	19	23	55	300524
125	1	2	2	67,5	19	25	70	300525
200	1 1/4	1 1/4	1 1/4	58	20	20	50	300526
160	1 1/4	1 1/2	1 1/2	63	20	23	55	300527
125	1 1/4	2	2	68,5	20	25	70	300528
160	1 1/2	1 1/2	1 1/2	66	23	23	55	300529
125	1 1/2	2	2	71,5	23	25	70	300530
125	2	2	2	74	25	25	70	300531




Zatvaračni vijak Serija 3010 - Unutrašnji šestougao


A technical drawing of a hexagonal plug valve. The drawing shows a side view of the valve body with a hexagonal plug. Dimension lines indicate the height of the valve body as 'L1' and the width of the plug as 'A'. A label 'CH1' points to the top of the valve body.

PN [bar]	A	L1	CH1	Tip
350	1/8	8	5	301001
350	1/4	10	7	301002
250	3/8	10	8	301003
225	1/2	10	10	301004
200	3/4	12	12	301005
160	1	12	17	301006
160	1 1/4	18	22	301007
160	1 1/2	20	24	301008


Spojница Serija 3012, Unutrašnji navoj

	PN [bar]	A	B	L1	L2	L3	CH1	Tip
	350	1/8	1/8	20	7	7	14	301201
	350	1/4	1/4	30	12	12	19	301202
	250	3/8	3/8	30	12	12	24	301203
	225	1/2	1/2	38	15	15	27	301204
	200	3/4	3/4	40	15	15	36	301205
	160	1	1	48	19	19	41	301206

Pravi adapter Serija 3018, 2x Navrtna matica

	PN [bar]	A	B	L1	CH1	CH2	CH3	Tip
	400	1/4	1/4	40,5	19	19	19	301802
	400	1/4	3/8	41,5	22	19	22	301811
	400	3/8	3/8	42,5	22	22	22	301803
	350	1/4	1/2	45,5	27	19	27	301812
	350	3/8	1/2	46	27	22	27	301813
	350	1/2	1/2	49,5	27	27	27	301804
	315	1/2	3/4	55	32	27	32	301814
	315	3/4	3/4	59	32	32	32	301806


90° Ugaoni adapter Serija 3024



PN [bar]	A	L1	CH1	Tip
400	1/8	21	11	302401
400	1/4	26	14	302402
400	3/8	29	19	302403
350	1/2	34	22	302404
350	5/8	38	27	302405
315	3/4	41	27	302406
250	1	45	33	302407
200	1 1/4	52	41	302408
160	1 1/2	59	48	302409
125	2	78	65	302410



90° Ugaoni adapter Serija 3042, Unutrašnji navoj




PN [bar]	A	L1	CH1	Tip
350	1/8	17	14	304201
350	1/4	22,5	19	304202
250	3/8	26	22	304203
225	1/2	31	27	304204
200	3/4	34,5	33	304205
160	1	41	41	304206
160	1 1/4	43	49	304207
160	1 1/2	53	65	304208
100	2	61	71	304209

T-adapter Serija 3050, Unutrašnji navoj

Technical drawing of a T-adapter. The drawing shows a side view of the component. A horizontal line with an arrow points to the top left port, labeled 'CH1'. A dimension line with arrows at both ends is labeled 'L1', indicating the length of the top section. A vertical dimension line with arrows at both ends is labeled 'A', indicating the height of the bottom section. The drawing uses standard engineering conventions, including hidden lines and section hatching.


PN [bar]	A	L1	CH1	Tip
350	1/8	17	14	305001
350	1/4	22,5	19	305002
250	3/8	26	22	305003
225	1/2	31	27	305004
200	3/4	34,5	33	305005
160	1	41	41	305006
160	11/4	43	48	305007
160	11/2	53	65	305008
100	2	61	71	305009

90° Ugaoni adapter Serija 3064, Spoljašnji navoj/Navrtna matica


	PN [bar]	A	B	L1	L2	CH1	CH2	Tip
	400	1/8	1/8	21	25	11	14	306401
	400	1/4	1/4	26	33	14	19	306402
	400	3/8	3/8	29	37	19	22	306403
	350	1/2	1/2	34	43	22	27	306404
	350	5/8	5/8	38	49	27	30	306405
	315	3/4	3/4	41	53,5	27	32	306406
	250	1	1	45	60,5	33	41	306407
	200	1 1/4	1 1/4	57	64	41	50	306408
	160	1 1/2	1 1/2	59	75,5	48	55	306409
	125	2	2	78	91	65	70	306410




T-adapter Serija 3070, Navrtna matica

	PN [bar]	A	L1	CH1	CH2	Tip
	400	1/8	25	11	14	307001
	400	1/4	33	14	19	307002
	400	3/8	37	19	22	307003
	350	1/2	43	22	27	307004
	350	5/8	49	27	30	307005
	315	3/4	53,5	27	32	307006
	250	1	60,5	33	41	307007
	200	1 1/4	64	41	50	307008
	160	1 1/2	75,5	48	55	307009
	125	2	91	65	70	307010

Uvrtni adapter Serija 3072, elastična zaptivka


	PN [bar]	A	B	L1	L2	L3	CH1	Tip
	350	1/8	1/8	14,5	8	8	14	307201
	350	1/4	1/4	19	11	12	19	307202
	250	3/8	3/8	20,5	12	12	22	307203
	225	1/2	1/2	24	14	14	27	307204
	200	5/8	1/2	26	16	14	27	307205
	200	3/4	3/4	28	16	16	32	307206
	160	1	1	32	19	18	41	307207
	160	1 1/4	1 1/4	37	20	20	50	307208
	160	1 1/2	1 1/2	40	23	22	55	307209
	100	2	2	45,5	25	24	70	307210

Podesivi ravni uvrtni priključak Serija 3073, Spoljašnji navoj/Navrtna matica, elastična zaptivka


	PN [bar]	A	B	L1	L2	CH1	CH2	Tip
	350	1/8	1/8	20	8	14	14	307301
	350	1/4	1/4	25	12	19	19	307302
	250	3/8	3/8	27	12	22	22	307303
	225	1/2	1/2	31	14	27	27	307304
	200	5/8	1/2	35	14	27	30	307305
	200	3/4	3/4	37	16	32	32	307306
	160	1	1	44,5	18	41	41	307307
	160	1 1/4	1 1/4	47	20	50	50	307308
	160	1 1/2	1 1/2	54,5	22	55	55	307309
	100	2	2	62	24	70	70	307310



Zatvorna kapica Serija 3079

	PN [bar]	A	L1	L2	CH1	Tip
	400	1/8	15	12	14	307901
	400	1/4	19	15	19	307902
	400	3/8	20	15	22	307903
	350	1/2	24	19	27	307904
	350	5/8	26	19	30	307905
	315	3/4	30	21	32	307906
	250	1	35	24,5	41	307907
	200	1 1/4	36	27	50	307908
	160	1 1/2	42	29,5	55	307909
125	2	45	30	70	307910	

90° Ugaoni adapter Serija 3080, 2x Navrtna matica

	PN [bar]	A	L1	CH1	CH2	Tip
	400	1/8	25	11	14	308001
	400	1/4	33	14	19	308002
	400	3/8	37	19	22	308003
	350	1/2	43	22	27	308004
	350	5/8	49	27	30	308005
	315	3/4	53,5	27	32	308006
	250	1	60,5	33	41	308007
	200	1 1/4	64	41	50	308008
	160	1 1/2	72,5	48	55	308009
	125	2	91	65	70	308010

Ilustracije nisu obavezujuće

Zadržavamo pravo na konstruktivne, dimenzione i promene materijala.

Pneumatika / Priključci i spojnice za pneumatiku / priključci / mlaznice za crevo / priključci - pocinkovani čelik BSI 5200

Verzija 5

138536 / Generisano 2026/33 SR

+381 11 2399521
balkan@stasto.eu
© STASTO Automatizacija d.o.o.

www.stasto.rs
Otvori seriju online
Strana 6 / 6

