

Ravna navojna priključnica Serija C-GAI-R



Osnovno tijelo s maticom i rezni prsten



B4-Rezni prsten






B3-Rezni prsten

Izvedba	Priključak s rezanim prstenom, s B3 ili B4-reznim prstenom
Navoj za pričvršćivanje na vijak	1/8...1 1/2"
Vanjski promjer cijevi	6...42mm
Materijal	Čelik pocinčan
Prema normi	EN ISO 8434-1 (DIN 2353)
Medij	neutralne tekućine i plinovi, koji ne napadaju upotrijebljene materijale
Temperatura medija	B3-Rezni prsten -40...+120°C B4-Rezni prsten NBR -35...+100°C (FKM na upit)
Radni tlak	Nazivni tlak prema tablici



Dimenzije



Osnovno tijelo

s B4-reznim prstenom

s B3-reznim prstenom

Seriya	PN [bar]	Promjer cijevi	G	L1	L2	L3	L4	CH1	CH2	Tip Osnovno tijelo	Tip s B4-prstenom	Tip s B3-prstenom
L	315	6	1/8	16	9	10	23,5	14	14	C-GAI06LR1/8X	C-GAI06ZLR1/8	C-GAI06LR1/8
		8	1/4	17	10	14	25	19	17	C-GAI08LR1/4X	C-GAI08ZLR1/4	C-GAI08LR1/4
		10	1/4	18	11	14	26	19	19	C-GAI10LR1/4X	C-GAI10ZLR1/4	C-GAI10LR1/4
		12	3/8	19	12	14	26,5	24	22	C-GAI12LR3/8X	C-GAI12ZLR3/8	C-GAI12LR3/8
		15	1/2	21	14	17	29	27	27	C-GAI15LR1/2X	C-GAI15ZLR1/2	C-GAI15LR1/2
		18	1/2	21	13,5	17	30	27	32	C-GAI18LR1/2X	C-GAI18ZLR1/2	C-GAI18LR1/2
	160	22	3/4	24	16,5	19	33	36	36	C-GAI22LR3/4X	C-GAI22ZLR3/4	C-GAI22LR3/4
		28	1	23,5	16	21,5	32,5	41	41	C-GAI28LR1X	C-GAI28ZLR1	C-GAI28LR1
		35	1 1/4	28,5	18	23,5	39,5	55	50	C-GAI35LR1 1/4X	C-GAI35ZLR1 1/4	C-GAI35LR1 1/4
		42	1 1/2	28,5	17,5	25,5	40,5	60	60	C-GAI42LR1 1/2X	C-GAI42ZLR1 1/2	C-GAI42LR1 1/2
S	630	6	1/4	19	12	14	27	19	17	C-GAI06SR1/4X	C-GAI06ZSR1/4	C-GAI06SR1/4
		8	1/4	19	12	14	27	19	19	C-GAI08SR1/4X	C-GAI08ZSR1/4	C-GAI08SR1/4
		10	3/8	20	12,5	14	28,5	24	22	C-GAI10SR3/8X	C-GAI10ZSR3/8	C-GAI10SR3/8
		12	3/8	20	12,5	14	28,5	24	24	C-GAI12SR3/8X	C-GAI12ZSR3/8	C-GAI12SR3/8
		14	1/2	23	15	17	33	30	27	C-GAI14SR1/2X	C-GAI14ZSR1/2	C-GAI14SR1/2
	400	16	1/2	23	14,5	17	33	30	30	C-GAI16SR1/2X	C-GAI16ZSR1/2	C-GAI16SR1/2
		20	3/4	26	15,5	19	37	36	36	C-GAI20SRX3/4	C-GAI20ZSR3/4	C-GAI20SR3/4
		25	1	27,5	15,5	21,5	39,5	41	46	C-GAI25SR1X	C-GAI25ZSR1	C-GAI25SR1
		30	1 1/4	32,5	19	23,5	45,5	55	50	C-GAI30SR1 1/4X	C-GAI30ZSR1 1/4	C-GAI30SR1 1/4
		38	1 1/2	34,5	18,5	25,5	49,5	60	60	C-GAI38SR1 1/2X	C-GAI38ZSR1 1/2	C-GAI38SR1 1/2

Ilustracije neobvezujuće

Zadržavamo pravo na konstrukcijske, dimenzijske i promjene materijala.

Pneumatika / Spojni elementi i spojnice / Rezni prstenasti priključci / Rezni prstenasti priključci - Pocičani čelik ISO 8434-1 (DIN 2353) / Ravna navojna priključna spojka Serija C-GAI-R

Verzija 8

138469 / Generirano 2026/38 HR

PROIZVEDENO U EUROPI

+381 11 2399521

balkan@stasto.eu

© STASTO Automatizacija d.o.o.

www.stasto.rs

Otvori seriju online

Stranica 2 / 2

