

Brtveni prstenovi Serija SE



SE- Vlakno



SE- PVC




SE- Najlon




SE- Aluminij

Materijali	Vlakno, PVC bijelo, Najlon, Aluminij
Medij	Stlačeni zrak, neutralni plinovi, Tekućine koje kemijski ne napadaju materijale
Temperatura medija	-20°C...+70°C, Aluminij -20°C...+250°C
Radni tlak	-1...60 bar


Brtveni prsten od Aluminija

	za navoj	D1	D2	S	Težina [g]	Tip
	M5	5,2	9	1	0,1	SE-M5-A
	G1/8"	10,3	14	1,5	0,2	SE-18-A
	G1/4"	13,5	18	1,5	0,4	SE-14-A
	G3/8"	17	22	1,5	0,5	SE-38-A
	G1/2"	21,5	27	1,5	0,8	SE-12-A

Brtveni prsten od najlona


	za navoj	D1	D2	S	Težina [g]	Tip
	M5	5	8	1,2	0,075	SE-M5-D
	G1/8"	10	14	1,8	0,15	SE-18-D
	G1/4"	13,2	18	1,8	0,25	SE-14-D
	G3/8"	17	21,4	1,8	0,30	SE-38-D
	G1/2"	21,5	25,4	2	0,40	SE-12-D

Brtveni prsten od Fiber

	za navoj	D1	D2	S	Težina [g]	Tip
	M5	5	8	1	0,075	SE-M5-F
	G1/8"	10	13	1,5	0,15	SE-18-F
	G1/4"	13,2	18	1,5	0,25	SE-14-F
	G3/8"	16,8	22	1,5	0,30	SE-38-F
	G1/2"	21	28	2	0,40	SE-12-F



Brtveni prsten od PVC-a bijelo

	za navoj	D1	D2	S	Težina [g]	Tip
	M5	5	8	1	0,075	SE-M5-K
	G1/8"	10	13,5	1,5	0,15	SE-18-K
	G1/4"	13,5	18	1,5	0,25	SE-14-K
	G3/8"	17	22	1,5	0,30	SE-38-K
	G1/2"	21	28	1,5	0,40	SE-12-K

Ilustracije neobvezujuće

Zadržavamo pravo na konstrukcijske, dimenzijske i promjene materijala.

Pneumatika / Spojni elementi i spojnice / Šuplji vijci / Brtve / Brtve

