


Dvojni nastavek Serija A-3105



| | |
|--------------------|---|
| Priključek | 1/8"...1"BSP |
| Material | Nerjavno jeklo 1.4571 |
| Medij | Stisnjen zrak, nevtralni plini, Tekočine, ki kemično ne napadajo materialov |
| Temperatura medija | -60°C...+200°C |
| Obratovalni tlak | Nazivni tlak po tabeli |

Dimenzije

|  | PN [bar] | A | B | L1 | L2 | L3 | CH1 | Tip |
|---|----------|-------|-------|-------|----|----|-----|----------|
| | 400 | G1/8" | G1/8" | G1/8" | 25 | 8 | 8 | 14 |
| 400 | G1/8" | G1/4" | G1/4" | 30 | 8 | 11 | 17 | A-310502 |
| 400 | G1/4" | G1/4" | G1/4" | 34 | 11 | 11 | 19 | A-310504 |
| 400 | G1/4" | G3/8" | G3/8" | 33 | 11 | 12 | 22 | A-310505 |
| 400 | G1/4" | G1/2" | G1/2" | 39 | 11 | 14 | 27 | A-310506 |
| 400 | G3/8" | G3/8" | G3/8" | 34 | 12 | 12 | 22 | A-310508 |
| 400 | G3/8" | G1/2" | G1/2" | 41 | 12 | 14 | 27 | A-310509 |
| 400 | G3/8" | G3/4" | G3/4" | 44 | 12 | 16 | 32 | A-310510 |
| 400 | G1/2" | G1/2" | G1/2" | 44 | 14 | 14 | 27 | A-310511 |
| 400 | G1/2" | G5/8" | G5/8" | 44 | 14 | 16 | 30 | A-310512 |
| 400 | G1/2" | G3/4" | G3/4" | 45 | 14 | 16 | 32 | A-310513 |
| 400 | G1/2" | G1" | G1" | 51 | 14 | 19 | 41 | A-310514 |
| 400 | G3/4" | G5/8" | G5/8" | 47 | 16 | 16 | 32 | A-310517 |
| 400 | G3/4" | G3/4" | G3/4" | 46 | 16 | 16 | 32 | A-310518 |
| 400 | G3/4" | G1" | G1" | 51 | 16 | 19 | 41 | A-310519 |
| 400 | G1" | G1" | G1" | 55 | 19 | 19 | 41 | A-310522 |

Slike niso zavezujoče

Pridržujemo si pravico do sprememb konstrukcije, mer in materialov

Pnevmatika / Vezni elementi in spojke / Ostali sortiment - P05 / Dvojna cevna spojka serija A-3105

Različica 4

190228 / Ustvarjeno 2026/24 SL

IZDELANO V EVROPI

+386 51 253 255

slovenia@stasto.eu

© STASTO AVTOMATIKA d.o.o.

www.stasto.si

Odpri serijo na spletu

Stran 1 / 1

